



LANTF.3-COMB

RÉFÉRENCES REFERENCES	COULEUR COLOR	FLUX LUMENS	OP	OPTIQUE BEAM ANGLE	PUISSANCE CONSUMPTION	ALIMENTATION POWER	
LANTF.3-27K-OP	2700 K	432 lm	8 =   8° 15 = ▲ 15° 30 = ▲ 30° 40 = ▲ 40° 60 = ▲ 60° 15X40 = ▲ 15x40° 10X60 = ▲ 10x60°		3 x 2 W	230 VAC	
LANTF.3-30K-OP	3000 K	454 lm				/	24 VDC
LANTF.3-40K-OP	4000 K	486 lm					
LANTF.3-60K-OP	6000 K	498 lm					
LANTF.3-R-OP		-			3 x 3 W		
LANTF.3-G-OP		-					
LANTF.3-B-OP		-			3 x 4 W	DMX	
LANTF.6-RGB-OP		-					
LANTF.6-RGB30K-OP		-					
LANTF.6-RGB40K-OP		-					

- 3 x LED CREE - IRC 85+  
3 x LED CREE - CRI85+
- 50 000 heures - L80 B10 à Ta = 25°C  
50 000 hours - L80 B10 at Ta = 25°C
- Aluminium anodisé, acier inoxydable A316L  
Aluminium finish, A316L stainless steel
- 50 cm de câble inclus  
50cm cable included
- 20°C ~ +40°C  
-20°C ~ +40°C

FINITION FINISH

- Inox
- Inox

OPTIONS OPTIONS

- IRC 90+ sur demande  
CRI90+ on request
- LANTF.3-COMB : grille en nid d'abeille  
LANTF.3-COMB: honeycomb
- Gestion DALI, DMX, 0-10V, KNX, Radiofréquence, Triac, Push Dim  
DALI, DMX control 0-10V, KNX, Radio Frequency, Triac, Push Dim control

