






LED3*ANTAR FIX 6



LANTF.6-COMB

RÉFÉRENCES REFERENCES	COULEUR COLOR	FLUX LUMENS	OP	OPTIQUE BEAM ANGLE	PUISSANCE CONSUMPTION	ALIMENTATION POWER
LANTF.6-27K-OP	2700 K	892 lm	8 = 8° 15 = 15° 30 = 30° 40 = 40° 60 = 60° 15X40 = 15x40° 10X60 = 10x60°		6 x 2 W	230 VAC / 24 VDC
LANTF.6-30K-OP	3000 K	938 lm				
LANTF.6-40K-OP	4000 K	1007 lm				
LANTF.6-60K-OP	6000 K	1037 lm				
LANTF.6-R-OP		-			6 x 3 W	24 VDC DMX
LANTF.6-G-OP		-				
LANTF.6-B-OP		-			6 x 4 W	24 VDC DMX
LANTF.6-RGB-OP		-				
LANTF.6-RGB30K-OP		-				
LANTF.6-RGB40K-OP		-				

6 x LED CREE - IRC 85+
6 x LED CREE - CRI85+

50 000 heures - L80 B10 à Ta = 25°C
50 000 hours - L80 B10 at Ta = 25°C

Aluminium anodisé, acier inoxydable A316L
Aluminium finish, A316L stainless steel

50 cm de câble inclus
50cm cable included

-20°C ~ +40°C
-20°C ~ +40°C

FINITION FINISH

Inox
Inox

OPTIONS OPTIONS

IRC 90+ sur demande
CRI90+ on request

LANTF.6-COMB : grille en nid d'abeille

LANTF.6-COMB: honeycomb

Gestion DALI, DMX, 0-10V, KNX, Radiofréquence, Triac, Push Dim
DALI, DMX control 0-10V, KNX, Radio Frequency, Triac, Push Dim control

