





**LED3\*RAIL E26X19**



- 
- 
- 
- 
- 

**EMBOUTS**  
END CAPS



LRE-E26X19-ENDCAP

**CLIPS**  
CLIPS



LRE-E26X19-CLIP

**JONCTIONS**  
JUNCTIONS



LRE-E26X19-JC90H



LRE-E26X19-JC90V



LRE-E26X19-JC180



LRE-E26X19-JC135H



LRE-E26X19-JC135V

RÉFÉRENCES REFERENCES	TRANSMITTANCE TRANSMITTANCE	LONGUEUR LENGTH
LRE-E26X19-2-T	93%	2000 mm 6.56 feet
LRE-E26X19-2-SD	80%	
LRE-E26X19-2-D <sup>(*)</sup>	65%	
LRE-E26X19-2-B ■	60%	

<sup>(\*)</sup> Diffuseur en rouleaux de 20 m en option  
<sup>(\*)</sup> 65 feet cover in option

- 1800K à 6500K, 2IN1, 3IN1, 4IN1 ou 5IN1  
1800K to 6500K, 2IN1, 3IN1, 4IN1 ou 5IN1
- Aluminium anodisé  
Aluminium finish

**OPTIONS** OPTIONS

Source lumineuse LED entre 400 à 4000 lm/m  
LED Light source between 136 and 1220 lm/feet  
Longueur de 2500 mm à partir de 30 pièces  
8.20 feet version available for quantities from 30pcs  
Finition sur demande à partir de 50 pièces  
Special finish on request for quantities from 50pcs  
Coupe, montage sur mesure : nous consulter  
Assembly, custom size: consult us